



# Model T1 Specifications

## CORD-ELECTRIC WALK-BEHIND SCRUBBER

Feature	Specification
<b>Scrubbing System</b>	
Cleaning path	15 in / 380 mm
Solution tank capacity	3.0 gallon / 11.4 liter
Productivity (per hour)	
Theoretical Max	15,920 ft <sup>2</sup> / 1,480 m <sup>2</sup>
Estimated Actual*	8,690 ft <sup>2</sup> / 810 m <sup>2</sup>
Solution Flow Rate	0.10 gpm / 0.38 lpm
Scrub Motors	0.4 hp / 0.3 kW
Scrub Motor Speed	2400 rpm
Brush down pressure	33 lb / 15 kg
Brush size	3.5 in / 89 mm
<b>Recovery System</b>	
Recovery tank capacity	4.5 gallon / 17.0 liter (Includes demisting chamber)
Vacuum fan	
Motor	1.2 hp / .88 kW
Stages	2-stage
Water lift	86 in / 2180 mm
Airflow	99 cfm / 2.8 m <sup>3</sup> /min
<b>Construction &amp; Power System</b>	
Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Power supply	120V or 230V
Frequency	50/60 Hz
Cable length	50 ft / 15 m
Electrical Safety Approvals	ETL Tested for UL & CSA Standards
<b>Dimensions / Weight / Sound level</b>	
Length	
Handle in working position	45.4 in / 1150 mm
Handle in folded position	27.3 in / 690 mm
Width	
Base	19.7 in / 500 mm
Squeegee	17.5 in / 440 mm
Height	
Base (folded handle for storage)	23.8 in / 600 mm
With handle up	34 in / 860 mm
Net weight	97 lb / 44 kg
Working weight (with water)	121 lb / 55 kg
Sound level** (operator's ear)	72 dBA
<b>Warranty</b>	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA