



# Model T2 Specifications

## BATTERY-POWERED WALK-BEHIND SCRUBBER-DRYER

Feature	
<b>Scrubbing System</b>	
Cleaning Path	43 cm/ 17 in. – Pad Assist
Solution Tank Capacity	26 liter / 6.9 gal.
Productivity (Per Hour)	
Theoretical Max	1,900 m <sup>2</sup> / 20,230 ft <sup>2</sup>
Estimated Actual	672 m <sup>2</sup> / 7,234 ft <sup>2</sup>
Variable Solution Flow Rate	0-1.1lpm / 0-.3 gpm
Brush Motor	.75 kW / 1 hp
Brush Operating Speed	230 rpm
Maximum Brush / Pad Pressure	23 kg / 50 lbs.
<b>Recovery System</b>	
Recovery Tank Capacity	36 liter/ 9.5 gal. – fully accessible and cleanable (Includes demisting chamber)
Vacuum Fan	
Motor	0.30 kW/ 0.4 hp
Stages	2
Vacuum Motor (Maximum)	1.84 cubic mm/minute / 65cfm
Sealed Water Lift	102 cm / 40 in.
Squeegee Description	69.5 cm/ 27.4 in. curved squeegee assembly with quick-change four sided rear blade
<b>Drive System</b>	
Caster Description	70 mm/ 2.75 in. diameter polyurethane
Wheel Description	178 x 38 mm/ 7 in. x 1.5 in. non-marking polyurethane
Batteries (12V system)	
Optional Lead Acid / Run time	(2) 12V, 85 AH / Up to 2 hours
Optional Gel / Run time	(4) 12V, 70 AH / Up to 1.75 hours
Optional Lead Acid/Run time	(2) 12V, 72 AH / Up to 1.75 hours (EU Only)
<b>Dimensions / Weight / Sound level</b>	
Length	112 cm / 44.1 in.
Width	
Body	44.1 cm / 17.4 in.
Scrub head	47.8 cm / 18.8 in.
Squeegee	69.5 cm / 27.4 in.
Height Maximum (Handle Lowest Position)	93 cm / 36.6 in.
Height Adjustable Handle - Range	12.6 cm / 5 in.
Net Weight	
Less Batteries	80 kg / 176 lbs.
With Batteries (2) 12V 70 AH gel	136 kg / 300 lbs.
Minimum Aisle Turn:	122 cm/ 48 in.
Sound Level	68 dBa
<b>Warranty</b>	24 months (or max 2000 running hours) on parts and 12 months (or max 1000 running hours) on labour, which ever comes first, excluding wear items