



REINVENT HOW THE WORLD CLEANS

i-mop[®] Lite

Walk-Behind Scrubber

Powerful Levels of Clean

Effectively clean in small and occupied spaces with the i-mop Lite. Its lightweight and maneuverable design helps ease the cleaning of tight spaces and obstacles. Increase your cleaning standards and productivity while enhancing the safety of operators and others.

Available Technologies



Lithium-Ion Batteries



Mobile and Accessible Cleaning

Lightweight with a minimal footprint, making it easy to pick up, carry, store and use. Wheels make it easy to push when not being operated.



Maneuverable Design

Easily clean in tight spaces with 360° movement. Park when needed with the stop and go parking stand.



Clean Efficiently

With Lithium-Ion battery technology, clean 15,069 ft² / 1,400 m² hourly with a run time of 45 minutes per charge.

Inside the i-mop® Lite

- 1. Simple intuitive controls** make it easy to operate and train.
- 2. Detachable tanks** make it easy to replace or change cleaning solution on the fly or empty recovery water in a sink offering very little down time.
- 3. Powerful 500 RPM motors** offer up to twice the speed of many conventional disk scrubbers.
- 4. Heavy-duty hinge for 360° steering**, making it highly maneuverable in small spaces around obstacles and under furniture.
- 5. Angle shutoff** automatically stops operation when the handle is placed below 32 degrees, helping prevent potential damage to the vacuum motor.
- 6. Rechargeable modular battery packs** for continuous run-time by swapping out and recharging with an extra set of batteries (single battery included, spare sold separately)
- 7. Counter rotating twin brushes with splash guards** push solution toward the center rather than splashing off to the side of the machine.



i-mop® Lite Specifications

| FEATURE | SPECIFICATION |
|--|---|
| Cleaning Path | 14.5 in / 368 mm |
| Productivity Theoretical Max (per hour) | 15,069 ft ² / 1,400 m ² |
| Brush RPM | 500 |
| Brush/Pad Pressure | 28.6 lbs / 13 kg |
| Solution Tank Capacity | .79 gal / 3 L |
| Recovery Tank Capacity | 1.06 gal / 4 L |
| Battery Run time (100% charge) [minutes - up to] | 45 |
| Battery Charge Time (100% charge) [up to hours*] | 3.5 hrs |
| Battery Run Time (one hour charging time) | 30 mins |
| Battery Voltage | 18.0 V (12 AH) |
| LxWxH (upright) | 13.4 x 16.9 x 47.2 in / 340 x 430 x 1,200 mm |
| Weight (with battery and water) | 36.38 lbs / 16.5 kg |
| Sound Level (operator's ear)** | 68 dB |

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.

** Run times are based on Continuous Scrubbing Run Times.*

*** For CE compliance, sound level is measured as an A-weighted sound pressure level per ISO 11201 and reported in accordance with ISO 4871.*

Specifications subject to change without notice.

For a demonstration or additional information, call **+1.800.553.8033** or email **info@tennantco.com**

**Singapore, Malaysia,
Taiwan, South Korea,
Bangladesh, Sri Lanka,
Pakistan, Guam:**
+65 9023 0231

**Thailand, Indonesia,
Vietnam, The Philippines,
Myanmar, Cambodia, Laos:**
+66 8 9890 4672

www.tennantco.ex
contactus@tennantco.com