



CREATING A CLEANER, SAFER, HEALTHIER WORLD.



5680 Specifications | Walk-Behind Floor Scrubber

Scrubbing System			
Cleaning path (3 paths available)	28-inch/700 mm	32-inch/800 mm	36-inch/900 mm
Solution tank capacity	30 gallon/114 liter		
Solution flow rates: Disk Standard:	.22 gpm/0.83 lpm		.30 gpm / 1.1 lpm
Cylindrical Standard & Disk Optional	.33 gpm / 1.25 lpm &		.44 gpm / 1.66 lpm &
Optional (Cylindrical & Disk)	.44 gpm / 1.66 lpm		.53 gpm/ 2.0 lpm
Conventional Mode Option	0–1.5 gpm / 0-5.7 lpm		0–1.5 gpm / 0-5.7 lpm
Scrub head types	Disk or cylindrical		
Scrub head motors (all paths / types)	(2) 0.75 hp/ 0.5 kW		
Brush speed: Disk/cylindrical	200 rpm/750 rpm		
Brush down pressure			
Disk (2-position)	100 & 200 lb/45.5 & 91 kg		
Cylindrical (1-position)	85 lb/39 kg		
Brush/pad driver quantity & dimensions			
Disk (D)	(2) 14-inch/355 mm	(2) 16-inch/405 mm	(2) 18-inch/455 mm
Cylindrical (L x D)	(2) 28 x 6-inch/ 700 x 150 mm	(2) 32x 6-inch/ 800 x 150 mm	(2) 36 x 6-inch/ 900 x 150 mm
Recovery System			
Recovery tank capacity	40 gallon/151 liter (Includes demisting chamber)		
Vacuum fan:			
Motor	0.8 hp/0.6 KW		
Stages	3-stage		
Water lift	73-inch/1,855 mm		
Propelling System			
Propel speed (variable to)	3.1 mph/5.0 km/h		
Batteries (36V system, charger included)			
Standard	(6) 6V, 235 AH		
Optional	(6) 6V, 335 AH		
Gradeability (Ramp climb)			
Full	6.0°		
Empty	8.0°		
Machine Dimensions / Sound level			
Length	63-inch/1,600 mm		
Width			
Body	28.25-inch/720mm	28.25-inch/720mm	28.25-inch/720mm
Scrub head	30-inch/760 mm	34-inch/865 mm	38-inch/965 mm
Squeegee	37.5-inch/955 mm	42-inch/1,065 mm	45.5-inch/1,155mm
Height	43-inch/1,090 mm		
Net weight			
Less batteries	403 lb/183 kg		
With 235 AH batteries	805 lb/366 kg		
With 335 AH batteries	985 lb/448 kg		
Minimum aisle turn	66.25-inch/1,680 mm	67-inch/1,700 mm	67.5-inch/1,725 mm
Sound level (operator's ear)	75 dBA		
Warranty	Please refer to your local Tennant representative for information.		

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA