



Model 3220 Specifications

UPRIGHT VACUUM

Feature		English / Metric
Brush Drive System		
Brush belt description	Dual, round drive belts	
Brush type	Single row, chevron pattern	
Brush size	2.25-inch/ 57 mm-diameter 12-inch/ 305 mm-length	
Brush power	0.1 hp/ 0.07 kW	
Brush motor RPM	6000 rpm	
Brush RPM	3000 rpm	
Brush height	Adjustable to 6 positions w/ manual dial	
Vacuum System		
Airflow @ 2.1-inch/ 53 mm Orifice	125 cfm/ 3.53 m³/h	
Waterlift at sealed Orifice	80-inch/ 2032 mm	
Vacuum motor type	Through flow, single stage; thermal protected	
Vacuum motor power	1.0 hp/ 0.7 kW	
Chassis & Body Construction		
Chassis & Body Construction	Rotationally-molded polyethylene	
Electrical		
Indicator light	Multi-signal light system for improved safety	
Electrical system	Printed circuit board protected	
Machine Dimensions		
Length	14.5-inch/ 370 mm	
Machine Width	14-inch/ 355 mm	
Height	47-inch/ 1195 mm	
Weight	21 lb/ 9.5 kg	
Filtration System		
Triple filtration system	Filter bag, vac motor filter, & post filter	
Vacuum filtration description	Vacuum bag 99.9 @ 0.3 microns	
Vacuum hose length	1.5 ft/ 0.46 m (4:1 stretch ratio)	
Vacuum bag capacity	Top fill design; 5L	
Power Cord		
Power cord length	40 ft/ 12 m	
Warranty	1 YEAR ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	